

TECHNICAL SPECIFICATIONS 459 02 LIGHT – Cfl-S1 Anthracite

FIRE BEHAVIOUR

CFL-S1

Type	Tufted non filled synthetic grass carpet	
Yarn Material	Polyamide	
Yarn Quality	Environmental friendly, free von led and cadmium, according REACH-norm	
Primary Backing	100% PP woven, black with fleece, UV stabilized appr. $\pm 135\text{g/m}^2$	
Secondary Backing	SBR Pre coat, $\pm 836\text{ g/m}^2$ with drainage holes	
Tuft gauge	3/8'	
Pile Height	approx. 18 mm	+/- 10%
Total Height	approx. 20 mm	+/- 10%
Pile gross weight	approx. 966 g/m ²	+/- 10%
Total weight	approx. 1.937 g/m ²	+/- 10%
# Stitches / 10 cml	± 14	
# Stitches per m ²	approx. 14.700/m ²	+/- 10%
UV Stability	5 years in N-Europe – DIN53387 standard (6000 hrs) Xenon Test Blue Scale > 7, Grey Scale > 4 4 years in sunny regions	
Roll width	4 meters	+/- 1%
Roll length	Target length 20,00 - 25,00 m	
Water permeability	> 60 l / min / m ²	
Shrinkage	Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting. Check the roll numbers before applying to make sure they are of the same colour badge	
Application	Fairs, Rooftops, Balcony, ...	

