

## TECHNICAL SPECIFICATIONS RTP819 NEW

Type	Tufted non filled synthetic grass carpet	
Yarn Material	100% Polyamide (nylon) extra stabilised, curled	
Yarn Dtex	7.600/8 ply	
Yarn Quality	environmental friendly, UV stabilized DIN 53387 standard	
Primary Backing	100% PP, double Thiobac with fibre locked fleece and glass fabric, black,UV stabilised	
Secondary Backing	Weight: approx. 280 g/m2	+/- 10%
	black latex compound with a base of SBR, with drainage holes	
	Weight: approx. 1000 g/m2	+/- 10%
Tuft gauge	3/16'	
Pile Height	approx. 32 mm	+/- 10%
Total Height	approx. 36 mm	+/- 10%
Pile gross weight	approx. 4.010 g/m2	+/- 10%
Total weight	approx. 5.290 g/m2	+/- 10%
# Knots per m2	approx. 75.600	+/- 10%
Lightfastness	Bluescale > 7 (according DIN 54004)	
Colourfastness	Greyscale > 4 (according DIN standard)	
UV Stability	8 years in moderate sunny regions EN 14836 6 years in sunny regions	
Roll width	4 and 2 meters	+/- 10%
Roll length	Target length approx. 20 m	
Water permeability	> 60 l / min / m2	
Shrinkage	Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
Batch information	Before installation make sure the first 4 digits of the roll number are equal	
Application	Tee, Driving Range	

