



ResiGrass

THE PREMIUM ARTIFICIAL GRASS

TECHNICAL SPECIFICATIONS RT605

Type	Tufted infill synthetic yarn	
Yarn material	100% Polyethylene, fibrillated, straight pile look	
Yarn type	8.800dTex	
Yarn quality	Environmental friendly – UV resistance	
Primary backing	Black uv resistant woven PP + fiber locked fleece	
	Weight: 164 g/m2	+/- 10%
Secondary backing	Black latex compound based on SBR with drainage	
	Weight: 1.000 g/m2	+/- 10%
Tuft gauge	3/16"	
Pile Height	12 mm	+/- 10%
Total Height	14 mm	+/- 10%
Pile gross weight	ca 1.300 g/m2	+/- 10%
Total weight	ca 2.464 g/m2	+/- 10%
# Knots per m2	ca 44.094	+/- 10%
# Piles per m2	88.188	+/- 10%
Roll width	3,72 - 4 meters	+/- 1%
Roll length	Max. 70m	
Colour	Green	
Marking Lines	lining possible	
Infill recommendation	Requires 15 kg/m² infill	
Shrinkage	Shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting	
Applications	Tennis, Paddle	

ResiGrass retains the right to modify each product with the objective to improve its quality according to the newest technology and as such shall not be legally liable for any and all deviations and/or non-compliance with these specifications.